



SIMATIC S7-400, analog input SM 431, non-isolated 16 AI, resolution 13 bit, +/-10 V, +/-20 mA, 4 - 20 mA 20 ms conversion time

Figure similar

Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) 	24 V; Only required for supplying 2-wire transmitters
<ul style="list-style-type: none"> Reverse polarity protection 	Yes
Input current	
from load voltage L+ (without load), max.	400 mA; for 16 connected, fully controlled 2-wire transmitters
from backplane bus 5 V DC, max.	100 mA
Power loss	
Power loss, typ.	2 W
Analog inputs	
Number of analog inputs	16
<ul style="list-style-type: none"> For voltage/current measurement 	16
permissible input voltage for voltage input (destruction limit), max.	20 V; 20 V DC permanent, 75 V DC for max. 1 s (duty factor 1:20)
permissible input current for current input (destruction limit), max.	40 mA
Constant measurement current for resistance-type transmitter, typ.	1.67 mA
Input ranges	
<ul style="list-style-type: none"> Voltage 	Yes
<ul style="list-style-type: none"> Current 	Yes
<ul style="list-style-type: none"> Thermocouple 	No
<ul style="list-style-type: none"> Resistance thermometer 	No
<ul style="list-style-type: none"> Resistance 	No
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> 1 V to 5 V <ul style="list-style-type: none"> Input resistance (1 V to 5 V) 	Yes 100 kΩ
<ul style="list-style-type: none"> -1 V to +1 V <ul style="list-style-type: none"> Input resistance (-1 V to +1 V) 	Yes 10 MΩ
<ul style="list-style-type: none"> -10 V to +10 V <ul style="list-style-type: none"> Input resistance (-10 V to +10 V) 	Yes 100 kΩ
Input ranges (rated values), currents	
<ul style="list-style-type: none"> -20 mA to +20 mA <ul style="list-style-type: none"> Input resistance (-20 mA to +20 mA) 	Yes 50 Ω
<ul style="list-style-type: none"> 4 mA to 20 mA <ul style="list-style-type: none"> Input resistance (4 mA to 20 mA) 	Yes 50 Ω
Cable length	
<ul style="list-style-type: none"> shielded, max. 	200 m
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	

<ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. • Integration time, parameterizable • Basic conversion time (ms) • Integration time (ms) • Interference voltage suppression for interference frequency f_1 in Hz • Basic execution time of the module (all channels released) 	13 bit Yes 55 / 65 ms 50 / 60 ms 50 / 60 Hz 1 040 ms; 880 / 1 040 ms
Encoder	
Connection of signal encoders	
<ul style="list-style-type: none"> • for voltage measurement • for current measurement as 4-wire transducer 	Yes; possible Yes
Errors/accuracies	
Temperature error (relative to input range), (+/-)	0.01 %/K
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> • Voltage, relative to input range, (+/-) • Current, relative to input range, (+/-) 	0.65 %; 1.0 % at 1 to 5 V; 0.65 % at ± 1 V, ± 10 V 0.65 %
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> • Voltage, relative to input range, (+/-) • Current, relative to input range, (+/-) 	0.25 %; 0.5% at 1 to 5 V; 0.25% at ± 1 V, ± 10 V 0.25 %; at ± 20 mA, 4 to 20 mA
Interrupts/diagnostics/status information	
Diagnostics function	No
Potential separation	
Potential separation analog inputs	
<ul style="list-style-type: none"> • Potential separation analog inputs • between the channels • between the channels and backplane bus • Between the channels and load voltage L+ 	No No No No
Isolation	
Isolation tested with	500 V AC/707 V DC, type test
Dimensions	
Width	25 mm
Height	290 mm
Depth	210 mm
Weights	
Weight, approx.	500 g

last modified:

3/12/2024 