## Data sheet 6GK7377-1AA00-0AA0



Compact Switch Module CSM 377 Connection SIMATIC S7-300 and up to 3 further nodes to Industrial Ethernet with 10/100 Mbit/s unmanaged switch, 4 RJ45 ports, External 24 V DC power supply LED diagnostics, S7-300 module, incl. electron. Equipment Manual on CD-ROM.

product type designation	
product brand name	SCALANCE
product type designation	CSM 377
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
<ul> <li>for network components or terminal equipment</li> </ul>	4
number of 100 Mbit/s SC ports	
• for multimode	0
interfaces / other	
number of electrical connections	
<ul><li>for power supply</li></ul>	1
type of electrical connection	
<ul> <li>for power supply</li> </ul>	2-pole terminal block
supply voltage, current consumption, power loss	
type of voltage / 1 / of the supply voltage	DC
<ul> <li>supply voltage / 1 / rated value</li> </ul>	24 V
<ul><li>power loss [W] / 1 / rated value</li></ul>	1.6 W
<ul> <li>supply voltage / 1 / rated value</li> </ul>	19.2 28.8 V
<ul><li>consumed current / 1 / maximum</li></ul>	0.07 A
<ul> <li>type of electrical connection / 1 / for power supply</li> </ul>	2-pole terminal block
<ul> <li>product component / 1 / fusing at power supply input</li> </ul>	Yes
• fuse protection type / 1 / at input for supply voltage	0, A / 60 V
ambient conditions	
ambient temperature	
<ul> <li>during operation</li> </ul>	0 60 °C
during storage	-40 +70 °C
during transport	-40 +70 °C
relative humidity	
<ul> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
protection class IP	IP20
design, dimensions and weights	
design	SIMATIC S7-300 device design
width	40 mm
height	125 mm
depth	118 mm
net weight	0.2 kg
fastening method	

OF year had but DIN and an experience	No
35 mm top hat DIN rail mounting	No No
• wall mounting	No
• S7-300 rail mounting	Yes
• S7-1500 rail mounting	No
product functions / management, configuration, engineering	
product function	
multiport mirroring	No
switch-managed	No
product functions / redundancy	
product function	
<ul> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	Yes
Parallel Redundancy Protocol (PRP)/Redundant Network	No
Access (RNA)	
standards, specifications, approvals	
certificate of suitability	
CE marking	Yes
cULus approval	Yes
KC approval	No
Regulatory Compliance Mark (RCM)	Yes
standard	
<ul> <li>for EMC interference emission</li> </ul>	EN 61000-6-4:2001
• for immunity to EMC	EN 61000-6-2:2001
• for safety / from CSA and UL	UL 508, CSA C22.2 No. 142
standards, specifications, approvals / hazardous environments	
certificate of suitability	
• ATEX	Yes
• UKEX	Yes
• IECEx	Yes
ULhazloc approval	Yes
<ul> <li>CCC / for hazardous zone according to GB standard</li> </ul>	Yes
FM registration	Yes
standards, specifications, approvals / other	
certificate of suitability	
RoHS conformity	Yes
standards, specifications, approvals / marine classification	
Marine classification association	
<ul> <li>American Bureau of Shipping Europe Ltd. (ABS)</li> </ul>	Yes
<ul> <li>French marine classification society (BV)</li> </ul>	Yes
DNV GL	Yes
<ul> <li>Korean Register of Shipping (KRS)</li> </ul>	Yes
Lloyds Register of Shipping (LRS)	Yes
Nippon Kaiji Kyokai (NK)	Yes
Polski Rejestr Statkow (PRS)	Yes
Royal Institution of Naval Architects (RINA)	Yes
product functions / general	
MTBF	144 a
reference code	
• according to IEC 81346-2	KF
<ul> <li>according to IEC 81346-2:2019</li> </ul>	KFE
Warranty period	5 a
further information / internet links	
internet link	
to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/de/view/109766358
• to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
• to website: Industrial communication	https://www.siemens.com/simatic-net
• to web page: SiePortal	https://sieportal.siemens.com/
• to website: Image database	https://www.automation.siemens.com/bilddb
J - · · · · · · ·	
• to website: CAx-Download-Manager	https://www.siemens.com/cax
<ul> <li>to website: CAx-Download-Manager</li> <li>to website: Industry Online Support</li> </ul>	
to website: CAx-Download-Manager     to website: Industry Online Support security information	https://www.siemens.com/cax

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

## **Approvals / Certificates**

## **General Product Approval**





**Declaration of Con**formity







**General Product Ap-**

For use in hazardous locations

Marine / Shipping













Marine / Shipping







NK / Nippon Kaiji Kyokai



Confirmation

**Environment** 

**Environment** 



last modified:

11/20/2024

