

### product type designation



### TIM 4R-IE DNP3

TIM 4R-IE DNP3 communications module for SIMATIC S7-300, S7-400, PC; with two RS232/RS485 Interfaces for DNP3- Communication via standard WAN networks and two RJ45 interfaces for DNP3 communication via IP-based networks (WAN or LAN).

transfer rate	
transfer rate	
<ul style="list-style-type: none"> <li>for Industrial Ethernet</li> </ul>	10 ... 100 Mbit/s
<ul style="list-style-type: none"> <li>according to RS 232</li> </ul>	9600 ... 115200 bit/s
interfaces	
number of interfaces / according to Industrial Ethernet	2
number of electrical connections	
<ul style="list-style-type: none"> <li>for external data transmission / according to RS 232</li> </ul>	2
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	1
type of electrical connection	
<ul style="list-style-type: none"> <li>of Industrial Ethernet interface</li> </ul>	RJ45 port
type of electrical connection	
<ul style="list-style-type: none"> <li>at interface 1 / for external data transmission</li> </ul>	9 pin Sub-D-connector, RS232 switchable to RS485
<ul style="list-style-type: none"> <li>at interface 2 / for external data transmission</li> </ul>	9-pole D-sub connector, RS232 can be switched to RS485
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	2-pole plugable terminal block
design of the removable storage	
<ul style="list-style-type: none"> <li>C-PLUG</li> </ul>	Yes
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage	24 V
supply voltage	20.4 ... 28.8 V
supply voltage / external / at DC / rated value	24 V
supply voltage / external / at DC / rated value	20.4 ... 28.8 V
consumed current	
<ul style="list-style-type: none"> <li>from backplane bus / at DC / at 24 V / maximum</li> </ul>	0.2 A
<ul style="list-style-type: none"> <li>from external supply voltage / at DC / at 24 V / maximum</li> </ul>	0.17 A
power loss [W]	4.6 W
product extension / optional / backup battery	Yes
type of battery	Lithium AA / 3.6 V / 2.3 Ah
backup current	
<ul style="list-style-type: none"> <li>typical</li> </ul>	100 µA
<ul style="list-style-type: none"> <li>maximum</li> </ul>	160 µA
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	0 ... 60 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +70 °C
relative humidity	
<ul style="list-style-type: none"> <li>at 25 °C / without condensation / during operation /</li> </ul>	95 %

maximum	
protection class IP	IP20
<b>design, dimensions and weights</b>	
module format	Compact module S7-300 double width
width	80 mm
height	125 mm
depth	120 mm
net weight	0.4 kg
<b>product features, product functions, product components / general</b>	
number of units	
• note	Number of TIMs per S7-300 / S7-400: 1
wire length	
• with RS 232 interface / maximum	6 m
• with RS 485 interface / maximum	30 m
<b>performance data / S7 communication</b>	
number of possible connections / for S7 communication	
• maximum	5; only via LAN
• with PG connections / maximum	2
• with OP connections / maximum	1
service	
• PG/OP communication	Yes
<b>performance data / telecontrol</b>	
suitability for use	
• node station	Yes
• substation	Yes
• TIM control center	Yes
protocol / is supported	
• DNP3	Yes
• SINAUT ST1 protocol	No
• SINAUT ST7 protocol	No
• Modbus RTU	Yes
product function / data buffering if connection is aborted	Yes; 200,000 data points with one master
number of DNP3 masters	
• for Ethernet / maximum	8
• with RS 232 interface / maximum	1
number of Modbus RTU slaves / maximum	1
<b>product functions / management, configuration, engineering</b>	
configuration software	
• required	SINAUT ST7 ES
storage location / of TIM configuration data	on the CPU or TIM
<b>product functions / time</b>	
product component / hardware real time clock	Yes
product feature / hardware real time clock w. battery backup	Yes
accuracy / of the hardware real time clock / per day / maximum	4 s
time synchronization	
• from NTP-server	Yes
<b>standards, specifications, approvals</b>	
reference code	
• according to IEC 81346-2:2019	KEC
<b>further information / internet links</b>	
internet link	
• to web page: selection aid TIA Selection Tool	<a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>
• to website: Industrial communication	<a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a>
• to web page: SiePortal	<a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a>
• to website: Image database	<a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>
• to website: CAx-Download-Manager	<a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber

threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit [www.siemens.com/cybersecurity-industry](https://www.siemens.com/cybersecurity-industry). Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

## Approvals / Certificates

### General Product Approval



[Declaration of Con-  
formity](#)



### EMV

### For use in hazardous locations

[KC](#)



[FM](#)

[CCC-Ex](#)



### Environment

[Confirmation](#)

last modified:

8/22/2024 