


*** spare part *** SIMATIC TP 177B 6" PN/DP STN 256 color display
 MPI/PROFIBUS DP protocol RS485/RS422/USB interface Ethernet 10/100
 interface printer interface slot for MMC configurable with WinCC flexible 2005



General information	
Product type designation	TP177B 6" PN/DP Color
Customer-specific configuration	Yes
Display	
Design of display	STN
Screen diagonal	5.7 in
Color display	Yes
Number of colors	256
Resolution (pixels)	
• Horizontal image resolution	320 pixel
• Vertical image resolution	240 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Control elements	Touch screen
Keyboard fonts	
• System keys	Yes
• Numeric keyboard	Yes
• alphanumeric keyboard	Yes
• hexadecimal keyboard	Yes
• Multi-key operation	No
Touch operation	
• Design as touch screen	Yes; analog, resistive
Connection type	
• Type of connection for mouse/keyboard/barcode reader	USB / USB / USB
Installation type/mounting	
Mounting position	vertical
maximum permissible angle of inclination without external ventilation	35°
Supply voltage	
Type of supply voltage	DC
Input current	
Current consumption (rated value)	0.24 A
Starting current inrush I ² t	0.5 A ² ·s
Processor	
Processor type	ARM, 200 MHz
Memory	
Type of memory	Flash / RAM
Memory available for user data	2 048 kbyte
Time of day	

Clock	
<ul style="list-style-type: none"> Type retentive synchronizable 	Hardware clock, synchronizable, no battery backup No Yes
Interfaces	
Interfaces/bus type	RS 232 optional, 1x RS 422, 1x RS 485, 1x Ethernet (RJ45) (max. 12 Mbit/s)
Number of industrial Ethernet interfaces	1
Number of RS 485 interfaces	1
Number of RS 422 interfaces	1
Number of USB interfaces	1; Up to 1 GB
PC card slot	No
CF card slot	No
Multimedia card/SD card slot	combined, from E-status 016 in connection with WinCC flexible 2008 SP1, MMC max. 128 MB / SD max. 512 MB
With software interfaces	No
Protocols	
Supports protocol for PROFINET IO	Yes
PROFIsafe	No
PROFIBUS	Yes
EtherNet/IP	Yes
Protocols (Ethernet)	
<ul style="list-style-type: none"> TCP/IP 	Yes
Protocols (terminal link)	
<ul style="list-style-type: none"> Sm@rtServer 	Yes
Further protocols	
<ul style="list-style-type: none"> MODBUS 	Yes
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
NEMA (front)	NEMA 4x, NEMA 12 (when installed)
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
cULus	Yes
EAC (formerly Gost-R)	No
Suitable for safety functions	No
Use in hazardous areas	
<ul style="list-style-type: none"> ATEX Zone 2 ATEX Zone 22 FM Class I Division 2 	No; certificate no longer available as of 1 October 2020 No; certificate no longer available as of 1 October 2020 Yes
Marine approval	
<ul style="list-style-type: none"> Germanischer Lloyd (GL) American Bureau of Shipping (ABS) Bureau Veritas (BV) Det Norske Veritas (DNV) Lloyds Register of Shipping (LRS) Polski Rejestr Statkow (PRS) 	Yes; only valid up to and including the HW release (see MLFB release notes in SIOS)! Yes; only valid up to and including the HW release (see MLFB release notes in SIOS)! Yes; only valid up to and including the HW release (see MLFB release notes in SIOS)! Yes; only valid up to and including the HW release (see MLFB release notes in SIOS)! Yes; only valid up to and including the HW release (see MLFB release notes in SIOS)! No; only valid up to and including the HW release (see MLFB release notes in SIOS)!
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> min. max. 	0 °C 50 °C
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> min. max. 	-20 °C 60 °C
Relative humidity	
<ul style="list-style-type: none"> Operation, max. 	90 %

Operating systems	
pre-installed operating system	Windows CE
configuration / header	
Message indicator	Yes
Alarm system (incl. buffer and acknowledgment)	Yes
Process value display (output)	Yes
Process value default (input) possible	Yes
Recipe management	Yes
Configuration software	
<ul style="list-style-type: none"> • Configuration tool • STEP 7 Basic (TIA Portal) • STEP 7 Professional (TIA Portal) • WinCC flexible Compact • WinCC flexible Standard • WinCC flexible Advanced • WinCC Basic (TIA Portal) • WinCC Comfort (TIA Portal) • WinCC Advanced (TIA Portal) • WinCC Professional (TIA Portal) 	<ul style="list-style-type: none"> WinCC flexible Compact Version 2005 or higher (to be ordered separately) No No Yes Yes Yes No Yes Yes Yes
Languages	
Online languages	
<ul style="list-style-type: none"> • Number of online/runtime languages 	5
Project languages	
<ul style="list-style-type: none"> • Languages per project 	32
Functionality under WinCC (TIA Portal)	
Libraries	Yes
Task planner	Yes
Help system	Yes
<ul style="list-style-type: none"> • Number of characters per info text 	70
Message system	
<ul style="list-style-type: none"> • Number of alarm classes • Number of messages • Bit messages <ul style="list-style-type: none"> — Number of bit messages • Analog messages <ul style="list-style-type: none"> — Number of analog messages • Telegram message procedure Alarm S • System messages HMI • System messages PLC • System event, more (SIMATIC S7, SINUMERIK, SIMOTION, ...) • Lines • Number of characters per message • Number of process values per message • Acknowledgment groups <ul style="list-style-type: none"> — Number of acknowledgement groups • Message indicator • acoustic feedback • First/last value 	<ul style="list-style-type: none"> 32 2 000 Yes 2 000 Yes 50 No Yes Yes No 1 80 8 99 Yes No Yes
Recipe management	
<ul style="list-style-type: none"> • Number of recipes • Data records per recipe • Entries per data record • Recipe memory 	<ul style="list-style-type: none"> 100 200 200 32 KB integrated Flash, expandable
Variables	
<ul style="list-style-type: none"> • Number of variables per device • Number of variables per screen • Number of variables • Initial values • Type Date & Time • Limit values 	<ul style="list-style-type: none"> 1 000 50 1 000 1 000 1 000 Yes

• Multiplexing	Yes
• Structures	No
Images	
• Number of configurable images	500
• Permanent window/default	Yes
• Start screen configurable	Yes
• Image selection by PLC	Yes
• Image number in the PLC	Yes
Image objects	
• Text objects	2 500 text elements
• Number of I/O fields per image	50
• Number of date/time fields	30
• Index of screen context	No
• Return	Yes
• Graphics object	Bit maps, icons, icon (full-screen), vector graphics
— Icons	500
— Icon (full screen)	50
Complex image objects	
• Status/control	With SIMATIC S7
• dynamic objects	Diagrams, bar graphs, sliders, analog display, invisible buttons
— Number of objects per project	500
— Number of curve diagrams per image	5
• Methods	Trend
• Bar graphs	
— Number of bars per chart	5
• Sliders	
— Number of slides per image	0
• Pointer instruments	
— Number of analog indicators per image	0
• Limit value lines	Yes
• Number of alphanumerical fields	1 000
— alphanumeric fields per image	100
• Number of numerical fields	1 000
— numerical fields per image	100
• Number of password fields	1 000
• Number of visible switches per project	1 000
— visible switches per image	100
— hidden switches per image	100
• Number of status switches per project	1 000
— Number of status switches per image	100
• Number of selector switches per project	1 000
— Selector switches per image	100
• Number of decade switches per project	0
— Decade switches per image	0
• Number of signal lamps per project	1 000
— Signal lamps per image	100
Attributes for dynamic objects	
• Color change	Yes
• X/Y movement	Yes
• Hide	Yes
• Angle of rotation	No
Lists	
• Number of text lists per project	300
• Number of text lists per image	10
• Number of entries per text list	30
• Number of graphics lists per project	100
• Number of graphic lists per image	10
• Number of entries per graphics list	30
Security	
• Number of user groups	50
• Number of user rights	32

• Password export/import	Yes
Data carrier support	
• PC card	No
• CF card	No
Logging through printer	
• Recording/Printing	Alarms, report (shift report), color print, hardcopy
Transfer (upload/download)	
• Transfer of configuration	MPI/PROFIBUS DP, serial, USB, Ethernet, by means of external storage medium, automatic transfer recognition
Process coupling	
• Connection to controller	S5, S7-200, S7-300/400, Win AC, PC (TCP/IP), SINUMERIK, SIMOTION, Allen Bradley (DF1), Mitsubishi (FX), Telemecanique (ADJUST), Modicon (Modbus), further non-Siemens drivers, see chapter "System interfaces"
• S7-1200	Yes
• S7-1500	No
• S7-200	Yes
— PPI (point-to-point)	Yes
— PPI network	No
— MPI	Yes
— PROFIBUS DP	Yes
— Ethernet	Yes
• S7-300/400	Yes
— MPI	Yes
— PROFIBUS DP	Yes
— PROFINET	Yes
• S5	Yes; only PROFIBUS DP
— serial	No
— PROFIBUS DP	Yes
• T1 505	No
• Allen Bradley (DF1)	Yes
• Allen Bradley (DF485)	Yes
• Mitsubishi (FX)	Yes
• Telemecanique (ADJUST)	No
• Telemecanique (Uni-Telway)	Yes; Only in combination with WinCC flexible
• OMRON (LINK/Multilink)	Yes
• Modicon (Modbus)	Yes
Functions	
• Key repeat	No
• TAB sequence	Yes
• Calculating functions	Yes
• Animate	Yes
• Menu tree editor	Yes
• Unit switchover	No
Service tools/configuration aids	
• Clean screen	Yes
• Touch calibration	Yes
• Backup/Restore manually	Yes
• Simulation	Yes
• Device switchover	Yes
• Delta transfer	Yes
• Monitoring function for battery and memory	No
• Trace (operation archive)	No
Expandability/openness	
• Open Platform Program	Yes
Peripherals/Options	
Peripherals	Printer
SIMATIC HMI MM memory card: Multi Media Card	Yes
Additional software components loadable	Yes
Dimensions	
Width of the housing front	212 mm
Height of housing front	156 mm

Mounting cutout, width	198 mm
Mounting cutout, height	142 mm
Overall depth	44 mm
Weights	
Weight (without packaging)	0.8 kg
Other	
free hotline	Yes

last modified: 12/8/2024 