

product type designation



CP 443-5 Basic

-- spare part -- communications processor CP 443-5 Basic for connection of SIMATIC S7-400 to PROFIBUS FMS, S5-compatible, PG/OP and S7 communication.

transfer rate	
transfer rate	
• at the 1st interface / according to PROFIBUS	9.6 kbit/s ... 12 Mbit/s
interfaces	
number of interfaces / according to Industrial Ethernet	0
number of electrical connections	
• at the 1st interface / according to PROFIBUS	1
type of electrical connection	
• at the 1st interface / according to PROFIBUS	9-pin Sub-D socket (RS485)
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
supply voltage	5 V
relative symmetrical tolerance / at DC	
• at 5 V	5 %
consumed current	
• from backplane bus / at DC / at 5 V / typical	1 A
• from external supply voltage / at DC / at 24 V / typical	1.2 A
power loss [W]	5 W
ambient conditions	
ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-400 single width
width	25 mm
height	290 mm
depth	210 mm
net weight	0.65 kg
product features, product functions, product components / general	
number of units	
• per CPU / maximum	14
• note	depending on CPU type
performance data / open communication	

number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	32
data volume <ul style="list-style-type: none"> as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	240 byte
performance data / FMS functions	
number of possible connections / for FMS connection / maximum	48
data volume / of the variables <ul style="list-style-type: none"> for READ job / maximum for WRITE job / maximum 	237 byte 233 byte
number of variables <ul style="list-style-type: none"> configurable from server to FMS partner loadable from server to FMS partner 	512 2640
performance data / S7 communication	
number of possible connections / for S7 communication <ul style="list-style-type: none"> maximum 	48
performance data / multi-protocol mode	
number of possible connections / of which 2 reserved for PG/OP communication / with multi-protocol mode / maximum	59
product functions / management, configuration, engineering	
configuration software <ul style="list-style-type: none"> required 	STEP 7 V5.2 SP1 or higher and NCM S7 for PROFIBUS
further information / internet links	
internet link <ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool to website: Industrial communication to website: Image database to website: CAX-Download-Manager to website: Industry Online Support 	https://www.siemens.com/tstcloud https://www.siemens.com/simatic-net https://www.automation.siemens.com/bilddb https://siemens.com/cax https://support.industry.siemens.com
security information	
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p>
Approvals / Certificates	
General Product Approval	
 EG-Konf.	Declaration of Conformity
 CCC	
 UL	KC
General Product Approval	
For use in hazardous locations	
 RCM	 ATEX
 FM	 IECEx
 Type Examination Certificate	 ATEX



[CCS \(China Classification Society\)](#)

[Confirmation](#)

last modified:

12/8/2024